

**TECHNICAL DATA
RR 200 ENDURO****CHASSIS**

Frame	Molybdenum steel with double cradle split above the exhaust port
Wheelbase	1477 mm
Max length	2167 mm
Max width	815 mm
Max height	1270 mm
Seat height	930 mm
Ground clearance	325 mm
Footrest height	410 mm
Dry weight	97,0kg (front 47,0 kg; rear 50,0 kg)
Fuel tank capacity	9,5 l.
Reserve	2,3 l.
Cooling system capacity	1,3 l.
Front suspension	Hydraulic USD fork with \varnothing 48 mm shaft
Rear suspension	Monoshock with progressive compound lever
Shock absorber stroke	135 mm
Front wheel travel	295 mm
Rear wheel travel	290 mm
Front brake	Wave disc \varnothing 260 mm and double-piston floating caliper
Rear brake	Wave disc \varnothing 240 mm and single-piston floating caliper
Front rim	21 x 1,6 - 36 fori
Rear rim	18 x 1,85 - 36 fori
Front tyre	90/90 - 21
Rear tyre	140/80 -18

ENGINE

Type	Single cylinder, 2-stroke, liquid-cooled
Bore	62 mm
Stroke	63 mm
Displacement	190.2 cc
Compression ratio	13,5:1
Exhaust Valve	BPV system
Starter	Electric starter
Ignition	AC Kokusan - digital CDI
Spark plug	NGK BR8ECM
Induction system	induction reed
Lubrication	Mixing with electrical pump
Carburettor	Keihin PWK 36
Clutch	wet multi-disc with reverse opening
Primary drive	Z.23/73
Transmission	6 gears
Final transmission	chain
Engine oil	SAE 10W/40
Consumption l/100 km	2,9
Pollution Co2 [g/km]	67